




PRODUCT CHARACTERISTICS				
	Standard	Requirement	Unit	Results
PRODUCT DESCRIPTION				
Surface treatment	-	-	-	Protecsol ^{TRIPLE ACTION}
Surface complex	-	-	-	100% pur PVC
Foam	-	-	-	CXP ^{COMFORT}
Thickness	EN 428	-	mm	3,9
Weight	EN 430	-	kg/m ²	1,95
Length	EN 426	-	lm	16 Standard
Width	EN 426	-	lm	1,5
SPORT PROPERTIES				
Shock absorption	EN 14808	≥ 25	%	-
Vertical deformation	EN 14809	≤ 3.5	mm	-
Energy return	NF P 90 203	≥ 0.31	m/s	-
Sliding coefficient	EN 13036-4	80 to 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	-
Ball speed	UEFA	50 to 65	cm	-
	ITF	-	-	-
TECHNICAL CHARACTERISTICS				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	-
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
CLASSIFICATION				
Fire	EN 13501-1	-	-	 Bfl-s1
Anti-bacterial activity (E. coli - S. aureus - MRSA) (3)	ISO 22196	-	-	> 99 % inhibits growth
DECLARATION OF PERFORMANCE				
	DOP n°xxx	-	-	Fire
INSTALLATION METHODS				
	Gerflor's recommendation		Unit	Results
Loose lay installation with double sided adhesive tapes	-	-	-	-
COLOUR RANGE				
 6570 Mint Green Canvas embossing				

(3) The implementation of an effective cleaning method is the best defence against infection



Health & Safety Life Cycle Analysis

ISO 14001

Recycling

TVOC
100
µg m³